



QUOTATION & OFFER

(Ref.No.20180305-USA-001)



Project Name:
Customer:
Offer Product: BLAZE 2600-II
Offer date: 2018-03-
Offer Include: Price list/Technical parameter/Configuration list
Offer from: NINGBO LEADWAY MACHINERY TECHNOLOGY CO.,LTD.
Offer prepared by: Mr.Guo (Business Manager)





1. Price List

To:	Issues date:	2018.03.05
Address:	Valid date:	2018.05.04
Tel / Mob.:	Incoterm:	FOB NINGBO
Email:	Payment terms:	As Term below
Destination Port:	Exchange rate:	1USD=6.3RMB
	Loading port:	Ningbo,China

No.	Items List & Description	Quantity (SETS)	Unit price (USD)	Amount (USD)
1	BLAZE 2600-II Injection machine	1		
	<u>Extra requirement:</u>			
1				
2				
3				
	Total	1		

Remarks:

- Above machine equipped with KEBA computer.
- Above machine meet with CE standard.
- About machine are servo motor driven.

Other Terms:

- Payment term: 30% by TT as deposit, 70% by TT before shipment.
- Delivery time: 30 working days after deposit.

Accepted by :

Offered by MR. Guo

For and behalf of

Ningbo Leadway Machinery Tech Co.,Ltd





2. Technical Parameter




Model	Unit	BLAZE 2600-II		
International size rating		1560		
Clamping Unit				
Clamping force	KN	2600		
Opening stroke	mm	560		
Space between tie-bars(H×V)	mm	630×580		
Max.mold height	mm	600		
Min mold height	mm	220		
Ejector stroke	mm	160		
Ejector force	mm	62		
Injection Unit				
		A	B	C
Screw diameter	mm	55	60	65
Screw L/D ratio	L/D	22	20	18.5







Theoretical shot volume	cm ³	642	848	996
Shot weight	g	584	772	906
	oz	20.6	27.2	32
Injection rate	g/s	200.2	238.3	279.6
Injection pressure	Bar	2190	1840	1568
Plasticing capacity	g/s	27.9	37.8	46.4
Screw speed	rpm	0-180		
Others				
Max.pump pressure	Bar	175		
Drive power	Kw	28.7		
Heating capacity	Kw	13.12		
Machine dimensions	m	6.7×1.8×2.0		
Machine weight	t	9.2		
Hopper capacity	Kg	50		
Oil tank capacity	L	380		

Mold Platen Sizes:





3. Machine Standard Configuration

Items		Brand/country
Servo System 	Controller	KEBA(Austria)
	Servo Motor	PHASE(ITALY)
	Servo Drive	INOVANCE
	Oil Pump	ECKERLE (Germany) or SUMITOMO (Japan)
Electric Unit 	Stroke transducer	NOVO or FLTECH(Germany)
	Breaker	EATON (USA) OR Schneider(France)
	Contactor	EATON (USA) OR Schneider(France)
	Air Switch	Schneider (France)
	Location /Speed Sensor	Schneider (France)
Hydraulic Unit 	Hydraulic Direction Valve	REXROTH(Germany) OR YUKEN (Japan)
	Proportion back-pressure valve	North man (Taiwan)
	Plasticizing hydraulic Motor	DAN DUN or ZHONGYI (ITALY)
	Hydraulic Hose	MANULI(ITALY) or Painter (JOINT VENTER)
	Hydraulic Sealing ring	All Italy
Others Unit	Mechanical safety	Standard
	Electric safety	Standard
	Mold close fast	Standard
	Injection Unit	Linear guide-way
	Air core	Option
	Hydraulic Core	Option
	T slots and screw holes	Standard
<p>Servo system Compared with the other manufacturers is big, Overload ability strong and stable.</p>		
		

FUHRUNG[®]

力维机械科技有限公司
LEADWAY MACHINERY TECHNOLOGY CO.,LTD

宁波市北仑区戚家山街道林唐东362号
No.362 Lintang East,Qijiashan Street, Beilun
District ,Ningbo, China 315803
+86 574 8911 7558 8307 5287

+86 574 8307 5285
0086-189 6838 1624
sales@fuhrung.com
fuhrungimm@gmail.com



4.

